

CC-E(WHT)/SIL


Analogue Multi-Sensor

Features

- ▶ SIL Level 2 approved
- > Ideal for use in oil and gas environments
- ▶ User selectable modes
- ▶ Incorporates Optical & Heat elements
- ▶ Removable, High Performance Chamber
- ▶ Twin LEDs allow 360° viewing green when polling, turn red in fire
- ▶ Pulsing/non-pulsing controlled from panel*
- ▶ Variable sensitivity
- **▶** Electronically Addressed
- ▶ LPCB & VdS approved to classes A1 & C



Model ACC-E(WHT)/SIL(HFP) is a Multi-Sensor, which which has been independently assessed and approved for use in a SIL2, low demand safety function with regards to random failure rates.



Specification	
Operating Voltage	17 – 41 VDC
Low Power Mode (typ)	120 μΑ
Quiescent Current (typ)	400 μA
Alarm Current (controlled by CIE)	9.1 mA (excluding remote indicator)
Transmission Method	Digital Communications Using ESP
Operating Temperature Range	-10 °C to + 50 °C
Operating Humidity	95% RH - Non Condensing (at 40 °C)
Storage Temperature Range	-30 °C to +60 °C
Storage Humidity	<80% RH at 60 ℃
Colour / Case Material	White / Polycarbonate
Weight (g)	95
Diameter (mm) / Height (mm)	100 / 45
Base Fixing Centres (mm)	48 ~ 74
Compatible Bases	YBO-BS, YBO-BSB2, YBN-R/3(SCI)
Approvals	LPCB & VdS approved to Classes A1, B & C

^{*}Control Panel compatibility required

Ordering Codes

Product Part Number

ACC-E(WHT)/SIL Analogue Multi-Sensor















