Conventional Weatherproof Sounder Strobe BANSHEE EXCEL LITE IP66



Features

- Robust design
- Low current consumption
- Easy to install
- Xenon beacon technology
- Maximum 110 dB(A) at 1 m (dependent on tone selected)
- 32 user-selectable tones
- Weatherproof IP66

Description

The BANSHEE EXCEL LITE IP66 combines the modern aesthetics of the multi-tone sounder and the very latest strobe technology to create an extremely efficient strobe/sounder combination for external applications. It is easily installed with robust terminations that can accept 2.5 mm² cables and a push and twist bayonet-fitting weatherproof base.

Available in a wide choice of lens colours^{*}, the BANSHEE EXCEL LITE IP66 will suit the majority of fire and security needs where a weatherproof conventional sound requires the backup of a visual alarm.

Specification			
Ordering code			BANSHEE EXCEL LITE IP66
Operating voltage			9 – 30 V dc
		min	6 mA
(dependant on tone selected) max		max	39 mA
Strobe	Current consumption		40 mA (@ 24 V dc)
	Nominal flash energy		1 W
	Flash rate		60/minute
	Lens colours available		Red/Clear*/Green*/Blue*/Amber*)
Operating Temperature Range			-20 °C to +55 °C
Maximum Sound Output (at 24 V dc) (dependant on tone selected)			110 dB(A) at 1 metre
Maximum Humidity			75%RH - Non Condensing (at 40 °C)
IP Rating			IP66
*Available upon request - place call for details			

*Available upon request – please call for details

Hochiki Europe (UK) Ltd. reserves the right to alter the specification of its products from time to time without notice. Although every effort has been made to ensure the accuracy of the information contained in this document it is not warranted or represented by Hochiki Europe (UK) Ltd. to be a complete and up-to-date description.