

# LEAKalarm

## CHQ-ARI

### Addressable Remote Indicator

#### Features

- ▶ High Intensity LED technology
- ▶ Addressable via Hand Held Programmer (TCH-B200)
- ▶ Up to 127 devices per loop
- ▶ Approved by VdS
- ▶ Loop-driven visual indication of a water leak
- ▶ Interfaced with the addressable loop.



#### Description

The CHQ-ARI is a loop-powered Addressable Remote Indicator, with high-intensity LEDs and a Fresnel lens design which produces a highly visible signal.

The unit can be used on the Standard ESP Base (YBN-R/3).

Specification	
Operating Voltage	17 - 41 VDC
Quiescent Current (typ)	280µA (300µA max)
Loop Current (when polled)	22mA
Alarm Current	4.5mA (5.4mA Max)
Operating Temp	-10 to +50 °C
Storage Temp	-30 to +60 °C
Max Humidity	95% HR (non-condensing)
Colour / Case Material	Ivory or White / ABS
Lens Colour/LED Colour	Transparent-Clear/Amber
Weight	88g
Dimensions (DiaxHxD)	100 x 38 x 46mm (With Base)
Approvals	VdS (G206053)

#### Ordering Codes

##### Product

Addressable Remote Indicator  
Addressable Remote Indicator (White)

##### Part Number

CHQ-ARI  
CHQ-ARI(WHT)