Conventional Beacon CWST-RW-S5



Features

- Approved to EN54-23, C & W categories
- Advanced optics ensures superior light coverage at low current draw
- Synchronised flash exceeds EN54-23 standard
- White light flash
- Soft start feature reduces power surges during system start-up

Description

CWST-RW-S5 features high output LEDs, advanced optics and an innovative lens design, providing outstanding Omni-directional light coverage at low current draw. Specifically designed for, and approved to meet EN54-23. The CWST-RW-S5 delivers outstanding quality, reliability and long operational life.

Specification				
Ordering Code	CWST-RW-S5			
Case Colour	Red			
Lens Colour	Clear			
LED Colour	White			
Cable Terminal Size	0.5-2.5 mm ²			
Material	Lens: PC			
	Body: PC-ABS			
Weight (g)	164			
Dimensions	Ø 100 mm x H 72 mm			
Operating Temperature	-25 °C to 70 °C			
Relative Humidity	93% ±3% non-condensing			
Ingress Protection	IP21C			
Operating Voltage EN54-23	12 to 29 V dc			
Average Current Consumption	26 mA @ 29 V dc			



Product Performance

	Wall mount W Class	Wall Mount W Class	Ceiling Mount C Class	Ceiling Mount C Class	
LED Colour	White	Red	White	Red	
EN54-23 Coverage Volume Code	W-2.4-9.0	W-2.4-6.2	C-3-9.5 C-6-9.5 C-9-9.5	C-3-9.4 C-6-8.6	
Installation Height (X)	2.4m	2.4m	3m 6m 9m	3m 6m	
EN54-23 Coverage (Y)	Cube YY 9.0m	Cube YY 6.2m	Cylinder Ø 9.5m	Cylinder Ø 9.5m 8.6m	
EN54-23 Coverage Volume	194m³	92m³	213m³ 425m³ 638m³	208m³ 348m³	
Flash Rate	0.5Hz	0.5Hz	0.5Hz	0.5Hz	
Operating Voltage Range	12 to 29V	12 to 29V	12 to 29V	12 to 29V	
Synchronisation	Automatically on power up, exceeds EN54-23 standard				

The Range

Part No.	Body Colour	Flash (LED) Colour	Base Option	Lens Colour
CWST-RW-S5	Red	White	Low Profile	Clear
CWST-RW-W5	Red	White	IP65/Deep	Clear
CWST-RR-S5	Red	Red	Low Profile	Clear
CWST-RR-W5	Red	Red	IP65/Deep	Clear
CWST-WW-S5	White	White	Low Profile	Clear
CWST-WW-W5	White	White	IP65/Deep	Clear
CWST-WR-S5	White	Red	Low Profile	Clear
CWST-WR-W5	White	Red	IP65/Deep	Clear

