

# Conventional Fixed Temperature Heat Detector (60°C) *DFJ-A3*



## Features

- ▶ Electronic linear heat detection
- ▶ Remote Indicator output
- ▶ Wide voltage range (9.5 ~ 30Vd.c.), can be installed on security systems
- ▶ Twin fire LED's allow 360° viewing
- ▶ Fixed Temperature Detector
- ▶ Approved by AS7240.5

## Description

Model DFJ-A3 is a 60°C Fixed Temperature Heat Detector using a thermistor and linearising circuit to provide an accurate linear response Heat Detector. A third terminal provides integral remote indicator output.

The DFJ-A3 is ideal for use where medium ambient temperatures exist, such as drying rooms or where Smoke Detectors are unsuitable because of the presence of steam or cooking fumes such as in a kitchen.

The DFJ-A3 is supported by a wide range of bases for different applications.

A third terminal provides remote indicator output.

Specification	
Ordering Code	DFJ-A3
Operating Voltage	9.5 - 30Vd.c.
Quiescent Current (typ)	35µA
Maximum Current in Alarm	80mA
Remote Indicator Drive	20mA (max) / 9.5-14mA (typ)
Operating Temperature Range	-10°C to +50°C
Storage Temperature Range	-30°C to +70°C
Maximum Humidity	95%RH - Non Condensing (at 40°C)
Ingress Protection Rating	IP63
Colour / Case Material	White / Polycarbonate
Weight (g) / Diameter (mm) / Height (mm)	76 / 100 / 38
Compatible Bases	YBN-R/6(WHT), YBO-R/6PA(WHT) YBO-R/6SK(WHT), YBO-R/6RN(WHT) YBO-R/6RS
Base Fixing Centres	48 ~ 74
Approvals	AS7240.5
	A1S

