

# FIREscape

## EL-16-AS Addressable 16 Meter Exit Sign Frame



*Fitted with EL-16G-R-AS (does not come with frame)*

### Features

- ▶ Complies With AS2293
- ▶ Available in 16 Meter and 24 Meter
- ▶ LED Status Indicator
- ▶ Hinged to fit any surface angle
- ▶ Integral Li-Po Standby Battery
- ▶ Fixes to Hochiki Test Switch Base (EL-TSB)
- ▶ Recess Adaptor Availability (EL-REC20)

### Description

The EL-16-AS is an illuminated exit sign intended to be visible up to a distance of 16 meter's. There are various models, each with a different arrow direction (indicating the direction of an exit). The frames require an exit sign lens (sold separately – see below)

<b>Lens Ordering code</b>		EL-16G-L-AS (left arrow) EL-16G-R-AS (right arrow) EL-16G-S-AS (straight)  EL-16G-AS (Reflective Worm Back plate and Rivets Assy for all single sided Exits)
<b>Operating Voltage</b>		24v – 40v
<b>Minimum Standby Operating Time</b>		+ 3 Hours
<b>Power consumption from line (W)</b>		0.4 Watt
<b>LED Lifetime</b>		+ 100,000 Hrs
<b>Battery</b>		7.4v /450mAh / 3.33Wh
<b>Dimensions (mm) including base</b>	<b>Wall mounted</b>	202L x 210H x 100D
	<b>Ceiling mounted</b>	202L x 205H x 100D
<b>Weight (g)</b>		150g
<b>Temp Range</b>		40°C
<b>Material</b>	<b>Cup and bracket</b>	Fire retardant
	<b>Lens</b>	Acrylic
<b>Fire class</b>		UL94 V-O
<b>Case color</b>		White (RAL 9003 "Signal White")
<b>Compliance</b>		AS2293, AS/NZS 60598.2.22, EN55015
<b>IP Rating</b>		IP 20 (IP44 Option Available)
<b>Base Compatibility</b>		EL-TSB