

Addressable 24Mtr Exit Sign

Features

- ▶ Complies with AS/NZS2293
- ▶ Available in 16 meter
- ▶ Visible at 24 meters
- ▶ LED technology
- Integral Li-Po stand-by battery
- Blade Type, hinged to fit to any surface angle
- Fixes easily to Hochiki base (EL-TSB)
- ▶ Recess Adapter Availability (EL-REC24)



Description

The EL-24-AS is an illuminated exit sign intended to be visible up to a distance of 24 metres. There are various models, each with a different arrow direction (indicating the direction of an exit). The frames require an exit sign lens (sold separately - see below)

Specification			
Cup and bar colour	White (RAL 9003 Signal White) & Black Available		
LED Lifetime	+ 100,000 Hrs		
Materials	Fire resistant PC + ABS plastic (FR3010) , Plexiglass-8N (sign)		
Fire class	UL94 V-O		
Viewing distance	24 m		
Standby Battery Operation time	3 hour +		
Battery	7.4V / 450mAh / 3.33Wh		
Dimensions (mm)	Wall Mount 328W x 280H x 100D (inc cup)		
	Ceiling Mount 328W x 290H x 100D (inc cup)		
Operating Temperature	0°C to +40°C		
Ingress Protection Rating	IP20 (IP66 Weatherproof variant available)		
Operating Humidity	RH 95% non-condensing		
Compliance	AS/NZS2293, AS/NZS60598.2.22, EN55015		
Weight including battery & Lens (g)	1,023		
Operating voltage DC	24V - 41V		
Energy consumption	1.03 W (charging)		
Life Sy Consumption	0.82 W (not charging)		











Ordering Codes

Туре	Direction		Ordering Code	Kit Contents	Description
24m Exit	Straight	Single Side	EL-24S KIT	EL-24-AS	Exit sign 24M Frame
				EL-24G-AS	Reflective worm , Back plate & Rivets assy
				EL-24G-S-AS	24M Lens - Straight
				EL-BAT450-AS	Battery
	Left Arrow	Single Side	EL-24L KIT	EL-24X-AS EL-24G-AS	Exit sign 24M Frame Reflective worm , Back plate & Rivets assy
				EL-24G-L-AS	24M Lens - Left Arrow
	Right Arrow	Single Side	EL-24R KIT	EL-24G-R-AS	24M Lens - Right Arrow
				EL-BAT450-AS	Battery
	Left Arrow	Double Side	EL-24D KIT	EL-24-AS	Exit sign 24M Frame
				EL-24G-AS	Reflective worm , Back plate & Rivets assy
	Right Arrow	Double Side		EL-24G-R-AS	24M Lens - Right Arrow
				EL-24G-L-AS	24M Lens - Left Arrow
				EL-BAT450-AS	Battery

Approvals















