

EL-DL3-AS

Addressable Open Area Down Light

Features

- ▶ Complies with AS/NZS2293
- ▶ LED technology
- ▶ Integral Li-Po stand-by battery
- ▶ Fixes easily to Hochiki test switch base (EL-TSB)
- ▶ Recess Adaptor Availability (NFW68/89-RA)

Description

EL-DL3-AS is an LED-based, addressable open area down light featuring one high-powered LED with a specially engineered dual surface free-form optic. The unit's body contains the electronics and the stand-by battery and features a bi-coloured LED indicating charge/fault status (green for charging, red for fault).

The unit has been designed to easily fit onto Hochiki's test switch base, the EL-TSB



Specification

Classification	C0: E6.3 - C90: E6.3
Colour	White (RAL 9003 Signal White) & Black Available
LED Lifetime	+ 100,000 Hrs
Materials	Fire resistant PC + ABS plastic (FR3010)
Fire class	UL94 V-0
Standby Battery Operation time	3 hour +
Battery	7.4V / 450mAh / 3.33Wh
Dimensions (mm)	100D x 48H inc 8mm for EL-TSB base
Operating Temperature	0°C to +40°C
Ingress Protection Rating	IP20 (IP67 Weatherproof variant available)
Operating Humidity	RH 95% non-condensing
Compliance	AS/NZS2293, AS/NZS60598.2.22, EN55015
Weight (g)	100
Operating Voltage DC	24V - 41V
Energy Consumption	0.34 W (charging)
	0.13 W (not charging)

Classification & Mounting Height

	Mtr	2.1	2.4	2.7	3	3.3	3.6	4	4.5	5	6	7	8	9	10	15	20
C0	E6.3	7	7.6	8	8.4	8.6	8.8	9.2	9.4	9.4	8.8	8.2	7				
C90	E6.3	7	7.6	8	8.4	8.6	8.8	9.2	9.4	9.4	8.8	8.2	7				

Ordering Codes

Product

Addressable Corridor Down Light

Part Number

EL-DL3 KIT

Approvals

