

EL-REC16 & EL-REC24

Recess Exit Sign Adaptor Brackets

Features

- ▶ Allows 16m and 24m FIREscape exit signs to be flush mounted into suspended ceilings
- ▶ Spring-loaded clips provide secure fitting to most hollow ceiling materials
- ▶ Requires exit sign and mounting base (not supplied)



Description

These recess adaptor brackets allow a semi-flush fitting of the EL-16 and EL-24 exit signs. The brackets need to be fitted with an exit sign and a mounting base (not supplied) and are equipped with spring loaded clips for secure fixing to most hollow ceiling materials.

The brackets also feature a small inspection hole in the ceiling plate which allows sight of the bicoloured status LED on the exit sign cup within the ceiling void.

Specification

Adaptor bracket colour	White
Materials	Powder-coated metal
Dimensions (mm)	EL-REC16 - 250L x 120W x 110H EL-REC24 - 380L x 120W x 110H
Cut-out dimensions (mm)	EL-REC16 - 220L x 90W EL-REC24 - 350L x 90W
Maximum Ceiling thickness (mm)	35
Weight (g)	EL-REC16 - 500 EL-REC24 - 650
Approvals	Luminaires awarded BSI Kitemark™

Order Codes

Product	Part Number
16m Recess Exit Sign Adaptor Brackets	EL-REC24
24m Recess Exit Sign Adaptor Brackets	EL-REC24