

### INTERNATIONAL ELECTROTECHNICAL COMMISSION IEC Certification Scheme for Explosive Atmospheres

for rules and details of the IECEx Scheme visit www.iecex.com

Ce	rtifi	cate	N	٥	

IECEx SIR 08.0105X

issue No.:2

Status:

Current

Garrone

Date of Issue:

2011-02-22

Page 1 of 4

Certificate history: Issue No. 2 (2011-2-22) Issue No. 1 (2009-8-24) Issue No. 0 (2008-11-25)

Applicant:

**KAC Alarm Company Limited** 

KAC House Thornhill Road North Moons Moat Redditch B98 9ND **United Kingdom** 

Electrical Apparatus:

Waterproof Manual Break Glass Fire Alarm Call Point Models WCP\*\*

Optional accessory:

Type of Protection:

Intrinsic Safety and Dust

Marking:

Ex ia IIC T4 Ga (-20°C < Ta < 70°C) Ii = 500mA, Ui = 30V, Pi = 1W

Ex iaD T135°C Da

(-20°C < Ta < 40°C) when Pi = 0.75W (-20°C < Ta < 70°C) when Pi = 0.65W

Approved for issue on behalf of the IECEx

Certification Body:

D R Stubbings BA MIET

Position:

Certification Manager

Signature:

(for printed version)

Date:

2011-02-22

1. This certificate and schedule may only be reproduced in full.

2. This certificate is not transferable and remains the property of the issuing body.

3. The Status and authenticity of this certificate may be verified by visiting the Official IECEx Website.

Certificate issued by:

SIRA Certification Service Rake Lane Eccleston Chester CH4 9JN United Kingdom





Certificate No.:

IECEx SIR 08.0105X

Date of Issue:

2011-02-22

issue No.: 2

Page 2 of 4

Manufacturer:

**KAC Alarm Company Limited** 

KAC House Thornhill Road North Moons Moat Redditch B98 9ND United Kingdom

### Manufacturing location(s):

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended.

### STANDARDS:

The electrical apparatus and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards:

IEC 60079-0: 2004

Electrical apparatus for explosive gas atmospheres - Part 0: General requirements

Edition: 4.0

IEC 60079-11: 2006

Explosive atmospheres - Part 11: Equipment protection by intrinsic safety "i"

Edition: 5

IEC 60079-26: 2006

Explosive atmospheres - Part 26: Equipment with equipment protection level (EPL) Ga

Edition: 2

IEC 61241-0: 2004

Electrical apparatus for use in the presence of combustible dust - Part 0: General

requirements

Edition: 1 IEC 61241-11 : 2005

Electrical apparatus for use in the pressence of combustible dusts - Part 11: Protection by

Edition: 1

intrinsic safety 'iD'

This Certificate does not indicate compliance with electrical safety and performance requirements other than those expressly included in the Standards listed above.

### **TEST & ASSESSMENT REPORTS:**

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in

### Test Report:

GB/SIR/ExTR08.0146/00 GB/SIR/ExTR09.0135/00 GB/SIR/ExTR11.0041/00

### Quality Assessment Report:

GB/SIR/QAR08.0020/00



Certificate No.:

IECEx SIR 08.0105X

Date of Issue:

2011-02-22

Issue No · 2

Page 3 of 4

### Schedule

### EQUIPMENT:

Equipment and systems covered by this certificate are as follows:

The Waterproof Manual Break Glass Fire Alarm Call Point Models WCP\*\* is an electrical switch which is operated manually by breaking a glass cover or pressing an optional re-settable frangible element. This releases a plunger, which activates a micro-switch. Options allow the fitting of single or double pole; single or double throw contacts, various resistors and diode combinations together with LED indication all mounted on a printed circuit board, all housed in a plastic enclosure. Terminations are made via a four-way terminal. The call point enclosure can be in different colours. A separate test key permits testing and re-setting of the call point.

The following models are included:

WCP1A - Normally open contact with series monitoring resistor

WCP1B - Normally open contact with series monitoring resistor (Savwire model)

WCP2A - Normally open contact with series monitoring resistor and LED network

WCP2B - Normally open contact with series monitoring resistor and LED network (Savwire model)

WCP3A - Normally open or normally closed single pole with single throw contacts

WCP4A - Normally open or normally closed double pole with single throw contacts

WCP7A - Selectable resistor/diode network, normally open single pole with single throw contacts

WCP7B - Selectable resistor/LED network, normally open single pole with single throw contacts

### CONDITIONS OF CERTIFICATION: YES as shown below:

1	The equipment enclosure is made of plastic. By virtue of its shape, design and position of use, it is
	assessed that the Equipment is not considered to be an electrostatic risk; however, the Equipment must
	not be installed in a position where it may be subjected to an excessive air/fluid flow or be subjected to
	rubbing that may cause an electroctatic build-up



_				
( 'Ar	すけいへ	ate	NI.	$\sim$
001	UIII	alc	14	ν

IECEx SIR 08.0105X

Date of Issue:

2011-02-22

Issue No.: 2

Page 4 of 4

	- this Issue introduced the following changes:	
	The option to fit an earth strap at the rear of the enclosure was endorsed.	
sue 2	- this Issue introduced the following changes:	
	The introduction of a distributors label in the name of Apollo was recognized.	