FIREwave[®]

Wireless Weatherproof Wall Sounder

RSM-WS/W



Features

- 3 Tones, adjustable volume up to 100 dB(A)
- ▶ Bi-directional wireless communication
- Automatic wireless channel hopping
- Easy and cost-effective additions to existing wired systems
- ▶ Compliant with current EN54 European standards and BS5839
- ▶ IP66
- Also available in white
- Internal use model also available

Description

The RSM-WS/W Weatherproof Wall Sounder is a fully intelligent wireless alarm signalling unit, providing a signalling solution for a wide variety of system sizes and types and is suitable for exterior use.

Sounder parameters are programmed via the Translator Module (RSM-WTM) and a PC link. The Translator Module automatically manages sounder radiated power depending on the device communication quality. All wall sounders can then adjust their frequency and radiated power output in accordance with the signal quality received from the Translator Module.

The Sounder comes as standard with three tones and is fitted with a volume control which is adjustable up to a maximum output of 100dB(A).

The device is fully controllable from the Control Panel via the Translator Module and offers the same level of flexibility as a standard addressable loop sounder.

Ordering Codes	RSM-WS/W(RED) RSM-WS/W(WHT)	
Communication range with Translator Module	150 m (open space)	
Operating frequency	868 - 870 MHz	
Modulation type	Frequency Shift Keying	
Number of operating channels	7	
Time period between wireless signal transmissions	From 7 seconds to 1 minute	
Power supply (dual 3V lithium batteries)	1 x Primary Cell (CR123A)	1 x Secondary Cell (CR123A)
Capacity	1.2 Ahr	1.2 Ahr
Estimated battery life*	3 years	3 months
Operating temperature range	-25 °C to +50 °C	
IP Rating	IP66	
Radiated power	0.01 to 3 mW (typical)	
Sounder output	100 dB(A) at 1 metre	
Dimensions (mm)	H110 x W110 x D105	

^{*}dependent on time period between wireless signal transmissions

World Class Leaders in Fire Detection Since