MARINE WCP1A

Conventional Marine Approved Weatherproof Manual Call Point

Features

- ▶ Complies with EN54-11
- ▶ Push-fit terminals can accommodate up to a 2.5mm² solid conductor.
- ▶ Other colours available on request
- ▶ IP rated to IP67
- ▶ Approved by GL.



Description

The WCP1A is a Conventional Marine Approved Weatherproof call-point based upon the industry standard KAC world series housing and features easy to install, push-fit wiring terminals. The unit features a 'Non Frangible Plastic' element and a weatherproof Housing to IP67, which means it can be mounted in the most severe environmental conditions without water ingress.

Specification			
Ordering Codes	Manual Call Point	WCP1A	
	Non-Frangible Element	KAC/EWS/HE	
Nominal operating resistance	470Ω	470Ω	
Maximum contact resistance	200Ω	200Ω	
Operating Temperature Range	-25°C to +70°C	-25°C to +70°C	
Relative humidity	0-95% non-condensing	0-95% non-condensing	
Storage temperature	-30°C to +70°C	-30°C to +70°C	
Max humidity	95%RH - Non condensing	95%RH - Non condensing (at 40°C)	
Ingress Protection (IP) Rating	IP67	IP67	
Colour / Case Material	Red/ABS	Red/ABS	
Weight (g) / Dimensions (mm)	234 / W98 x H93 x D71	234 / W98 x H93 x D71	
Approvals	GL	GL	







