

## Recess Base Adaptor YBN-UA(WHT)



*(shown with base fitted – not supplied)*

### Features

- ▶ Allows YBN-R/3(WHT) base and ALK-ASN analogue sensor to be flush mounted
- ▶ Supplied with fixing brackets
- ▶ Colour-matched to existing white sensor
- ▶ Sturdy construction, easy to install
- ▶ Tested by CSIRO
- ▶ AS1670.1-2015 Compliant

### Description

Model YBN-UA(WHT) is a mounting adaptor for ALK-ASN analogue sensor and YBN-R/3(WHT) base. The YBN-UA allows a base and head to be flush mounted by providing a recess fixing the ceiling.

It is supplied with a fixing clamp kit (YYA-A) which secures the YBN-UA within a pre-cut hole up to a maximum ceiling thickness of 30mm.

<b>Specification</b>	
Ordering Code	YBN-UA(WHT)
Operating Temperature Range	-10°C to + 50°C
Storage Temperature Range	-30°C to + 60°C
Maximum Humidity	95%RH - Non Condensing (at 40°C)
Colour / Material	White / ABS
Weight (g) / Diameter (mm) / Height (mm)	65 / 140 / 44
Height when fitted flush (mm)	7
Drilled Hole Size (mm)	115
Compatible Bases	YBN-R/3(WHT)
Fixing Centres (mm)	48 ~ 74